





Silmet Composites (Classification according to Directive 790/2009/EC)

Date of issue: 25.6.15 Supercedes version of: 07.11.13 Rev. 4

### SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

**Product name**: ProFil, ProVeneer

Manufacturer: Silmet Ltd.
Address: 12 Hassadna St.

Industrial Zone, Or Yehuda

6022011 Israel

Telephone: + 972 3 7353000

**Product use:** 

Intended Use: Dental product

Limitations on use: For use by dental professionals Specific Use: Composite restorative material

### **SECTION 2: HAZARDS IDENTIFICATION**

### 3.1 Emergency Overview

Specific Physical Form: Paste

Odor, Color, Grade: Slightly acrylate odor, tooth colored various shades

General Physical Form: Solid

Immediate helath, physical an environmental hazards: May cause allergic skin reaction.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredient regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

#### 3.2 Potential Health Effects

**Eye Contact:** Moderate Eye Irritation: Signs/symptoms may include localized redness, swelling, pain, tearing and blurred or hazy vision.

**Skin Contact:** Moderate Skin Irritation: Signs/symptoms may include localized redness, swelling, itching and dryness.

Allergic Skin Reaction (non photo induced): Signs/symptoms may include redness, swelling, blistering and itching **Inhalation:** Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, nose and throat pain.

**Ingestion:** Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

## **SECTION 3: INGREDIENTS**

Ingredient	C.A.S. No.	% by Wt
Barium aluminosilicate	65997-18-4	60-70
Fumed Silica	1129545-52-5	5-15
Bisphenol A Diglycidyl Ether Dimethacrylate (Bis –GMA)	1565-94-2	5-15
Triethylene Glycol Dimethacrylate (TEGDMA)	109-16-0	3-7
Urethanedimethacrylate	72869-86-4	1-5
Camphorquinone	10373-78-1	0.01-0.3
Ethyl-4-dimethylaminobenzoate	10287-53-3	0.01-0.3
Butylated Hydroxytoluene (BHT)	128-37-0	0.001-0.1
Titanium Oxide	1317-70-0	0.1-0.5
Iron Oxide	1317-61-9	Trace







Silmet Composites (Classification according to Directive 790/2009/EC)

Date of issue: 25.6.15 Supercedes version of: 07.11.13 Rev. 4

### **SECTION 4: FIRST AID MEASURES**

The following first aid recommendations are based on assumption that appropriate personal and industrial hygiene practices are followed.

Eye Contact: Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

**Skin contact**: Remove contaminated clothing and shoes. Immediately flush skin with large amounts of water. Get medical attention. Wash contaminated clothing and clean shoes before reuse.

**Inhalation**: Remove person to fresh air. If signs/symptoms persist, get medical attention.

If swallowed: Do not induce vomiting unless instructed to do so by medical personnel.

Give victim 2 glasses of water. Never give anything by mouth to unconscious person. Get medical attention.

## **SECTION 5: FIRE FIGHTING MEASURES**

## 5.1 Flammable properties

Auto ignition temperatureNot data availableFlash pointNot applicableFlammable Limits – LELNot applicableFlammable Limits – UELNot applicable

#### 5.2 Extinguishing media

Ordinary combustible material. Use fire extinguishers with class A extinguishing agents (e.g. water, foam)

### **5.3 Protection of fire fighters**

**Special Fire Fighting Procedures:** Wear full protective equipment (Bunker Gear) and a self contained breathing apparatus (SCBA)

Unusual Fire and Explosion Hazards: No unusual fire or explosion hazards anticipated.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

# SECTION 6: ACCIDENTAL RELEASE MEASURES

### **Accidental Release Measures:**

Evacuate unprotected and untrained personnel from hazard area. The spill should be cleaned up by qualified personnel. Ventilate the area with fresh air. Place in a closed container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible. Observe precautions from other sections. Collect as much of the spilled material as possible. Clean up residue.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state and federal regulation.

### **SECTION 7: HANDLING AND STORAGE**

#### 7.1 Handling

Avoid eye contact. Avoid skin contact. A no touch technique is recommended. If skin contact occurs, wash skin with soap and water.

#### 7.2 Storage

Store in a cool, dry place. Store away from heat. Store away from oxidizing agents.







Silmet Composites (Classification according to Directive 790/2009/EC)

Date of issue: 25.6.15 Supercedes version of: 07.11.13 Rev. 4

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Engineering controls

Use in a well-ventilated area.

### 8.2 Personal Protective Equipment (PPE)

### 8.2.1 Eye/Face Protection

Avoid eye contact.

The following eye protection(s) are recommended: Safety Glasses with side shields.

#### 8.2.2 Skin Protection

Avoid skin contact. See Section 7.1 for additional information on skin protection.

## **8.2.3 Respiratory Protection**

Under normal use conditions, airborne exposures are not expected to be significant enough to require respiratory protection.

#### 8.2.4 Prevention of Swallowing

Do not ingest. Wash hands after handling and before eating.

### 8.3 Exposure Guidelines

IngredientAuthorityTypeLimitAdditional InformationButylated Hydroxytoluene(BHT)ACGIHTWA,2 mg/m³

inhalable, fraction and vapor

### SOURCE OF EXPOSURE LIMIT DATA:

ACGIH: American Conference of Governmental Industrial Hygienists

CMRG: Chemical Manufacturer Recommended Guideline OSHA: Occupational Safety and Health Administration

AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

Specific Physical Form: Paste

Odor, Color, Grade: Slight acrylate odor, tooth-colored various shade

General Physical Form: Solid

Autoignition temperature

Flash Point

Not Applicable

Flammable Limits - LEL

Not Applicable

Not Applicable

Flammable Limits - LEL Not Applicable

Flammable Limits - UEL Not Applicable

Boiling point Not Applicable

Density 1.9 g/cm3

Vapor Density Not Applicable

Vapor Pressure Not Applicable

Specific Gravity 1.9 [Ref Std: WATER=1]

pH Not Applicable
Melting point No Data Available

Solubility in WaterNegligibleEvaporation rateNot ApplicableKow - Oct/Water partition coefNot ApplicableViscosityNo Data Available







Silmet Composites (Classification according to Directive 790/2009/EC)

Date of issue: 25.6.15 Supercedes version of: 07.11.13 Rev. 4

### **SECTION 10: STABILITY AND REACTIVITY**

Stability: Stable.

Materials and Conditions to Avoid:

**10.1 Conditions to avoid:** Heat

**10.2 Incompatible Materials:** Strong oxidizing agents

Hazardous Polymerization: Hazardous polymerization will not occur.

**Hazardous Decomposition or By-Products** 

**Substance** Condition

Carbon monoxide During Combustion
Carbon dioxide During Combustion

### **SECTION 11: TOXILOGICAL INFORMATION**

Non toxic and high biocompatibility. Please contact the address listed on the 1<sup>st</sup> page of the MSDS for the Toxilogical information on this material and/or its components

### **SECTION 12: ECOLOGICAL INFORMATION**

ECOTOXICOLOGICAL INFORMATION: Not determined.

CHEMICAL FATE INFORMATION: Not determined.

### SECTION 13: DISPOSAL CONSIDERATIONS

#### **Waste Disposal Method:**

Dispose of completely cured (or polymerized) wastes in a sanitary landfill.

As a disposal alternative, incinerate uncured product in an industrial or commercial incinerator in the presence of a combustible material.

EPA Hazardous Waste Number (RCRA): Not regulated

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Since regulations vary, consult applicable regulations or authorities before disposal.

## **SECTION 14: TRANSPORTATION INFORMATION**

Please contact the number listed on the 1st page of this MSDS for Transport Information of this material

## **SECTION 15: Regulatory information**

This product is classified as a medical device under US and Canadian regulations and has been reviewed by the US Food and Drug Administration and Health Canada

## US FEDERAL REGULATIONS

#### **Hazard Categories:**

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

#### **CHEMICAL INVENTORIES**

Commercial use of this material is regulated by the FDA

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

### **SECTION 16: OTHER INFORMATION**







Silmet Composites (Classification according to Directive 790/2009/EC)

Date of issue: 25.6.15 Supercedes version of: 07.11.13 Rev. 4

NFPA Hazard Classification

**Health:** 2 Flammability: 1 Reactivity: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

## CAUTION: PRODUCT FOR PROFESSIONAL USE

The information on this safety sheet is based on presently available data and to our best knowledge for the correct handling of the product under normal conditions. Any use of this product in any way not indicated on this sheet or use of this product together with any other process/procedure will be exclusively under the user's responsibility.