

---

**1. Identification**

---

<b>Product identifier</b>	<b>Butane Fuel Canister</b>
<b>Other means of identification</b>	Not available.
<b>Recommended use</b>	For use only in portable gas appliances
<b>Recommended restrictions</b>	None known.
<b>Manufacturer/Importer/Supplier/Distributor information</b>	
<b>Manufacturer</b>	
<b>Company name</b>	Hollowick, Inc.
<b>Address</b>	100 Fairgrounds Dr. P.O. Box 305 Manlius, NY, 13104 United States
<b>Telephone</b>	Phone: 315-682-2163 Phone: 800-367-3015 (Toll free) Fax: 315-682-6948
<b>E-mail</b>	info@hollowick.com
<b>Emergency phone number</b>	1-800-255-3924 (ChemTel) 1-813-248-0585 (ChemTel) (Outside US)
<b>Supplier</b>	See above.

---

**2. Hazard identification**

---

<b>Physical hazards</b>	Flammable gases Gases under pressure Simple asphyxiants	Category 1 Liquefied gas Category 1
<b>Health hazards</b>	Not classified.	
<b>Environmental hazards</b>	Not classified.	
<b>WHMIS 2015 defined hazards</b>	Not classified	
<b>Label elements</b>		



<b>Signal word</b>	Danger	
<b>Hazard statement</b>	Extremely flammable gas. Contains gas under pressure; may explode if heated. May displace oxygen and cause rapid suffocation.	
<b>Precautionary statement</b>		
<b>Prevention</b>	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
<b>Response</b>	Leaking gas fire: Do not extinguish, unless leak can be stopped safely. In case of leakage, eliminate all ignition sources.	
<b>Storage</b>	Protect from sunlight. Store in a well-ventilated place.	
<b>Disposal</b>	Dispose of container in accordance with local, regional, national and international regulations.	
<b>WHMIS 2015: Health Hazard(s) not otherwise classified (HHNOC)</b>	None known	
<b>WHMIS 2015: Physical Hazard(s) not otherwise classified (PHNOC)</b>	None known	
<b>Hazard(s) not otherwise classified (HNOC)</b>	None known.	
<b>Supplemental information</b>	None.	

---

**3. Composition/Information on ingredients**

---

**Mixture**

Chemical name	Common name and synonyms	CAS number	%
Butane		106-97-8	95

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

#### 4. First-aid measures

<b>Inhalation</b>	If symptoms develop move victim to fresh air. If symptoms persist, obtain medical attention.
<b>Skin contact</b>	Flush with cool water. Wash with soap and water. Obtain medical attention if irritation persists. Clothing frozen to the skin should be thawed before being removed.
<b>Eye contact</b>	Flush with cool water. Remove contact lenses, if applicable, and continue flushing. Obtain medical attention if irritation persists.
<b>Ingestion</b>	Do not induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Never give anything by mouth if victim is unconscious or is convulsing. Obtain medical attention.
<b>Most important symptoms/effects, acute and delayed</b>	Direct contact with eyes may cause temporary irritation. Victim may not be aware of asphyxiation. Asphyxiation may bring about unconsciousness without warning and so rapidly that victim may be unable to protect themself.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Treat frost-bitten areas as needed.
<b>General information</b>	If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Avoid contact with eyes and skin. Keep out of reach of children.

#### 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Carbon dioxide. Dry chemical powder. Foam. Water spray.
<b>Unsuitable extinguishing media</b>	None known.
<b>Specific hazards arising from the chemical</b>	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
<b>Special protective equipment and precautions for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Fire-fighting equipment/instructions</b>	DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED. In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Do not direct water at source of leak or safety devices as icing may occur. Use water spray to cool unopened containers. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials. Cool containers exposed to flames with water until well after the fire is out.
<b>General fire hazards</b>	Extremely flammable gas. Contents under pressure. Pressurized container may explode when exposed to heat or flame.
<b>Hazardous combustion products</b>	May include and are not limited to: Oxides of carbon.

#### 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
<b>Methods and materials for containment and cleaning up</b>	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. If possible, turn leaking containers so that gas escapes rather than liquid. Use water spray to reduce vapors or divert vapor cloud drift. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. For waste disposal, see section 13 of the SDS.
<b>Environmental precautions</b>	Prevent further leakage or spillage if safe to do so. Do not discharge into lakes, streams, ponds or public waters.

## 7. Handling and storage

<b>Precautions for safe handling</b>	Keep away from heat, sparks, open flames, hot surfaces. - No smoking. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. All equipment used when handling the product must be grounded. Close valve after each use and when empty. Protect cylinders from physical damage; do not drag, roll, slide, or drop. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash thoroughly after handling. Use good industrial hygiene practices in handling this material. When using do not eat or drink.
<b>Conditions for safe storage, including any incompatibilities</b>	Keep away from heat, sparks and open flame. This material can accumulate static charge which may cause spark and become an ignition source. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS). Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Stored containers should be periodically checked for general condition and leakage. Keep out of reach of children.

## 8. Exposure controls/Personal protection

### Occupational exposure limits

#### Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value
Butane (CAS 106-97-8)	TWA	1000 ppm

#### Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Type	Value
Butane (CAS 106-97-8)	STEL	1000 ppm

#### Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Type	Value
Butane (CAS 106-97-8)	STEL	1000 ppm

#### Canada. New Brunswick OELs: Threshold Limit Values (TLVs) Based on the 1991 and 1997 ACGIH TLVs and BEIs Publication (New Brunswick Regulation 91-191), as amended

Components	Type	Value
Butane (CAS 106-97-8)	TWA	1900 mg/m <sup>3</sup> 800 ppm

#### Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Type	Value
Butane (CAS 106-97-8)	STEL	1000 ppm

#### Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety)

Components	Type	Value
Butane (CAS 106-97-8)	TWA	1900 mg/m <sup>3</sup> 800 ppm

#### Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21)

Components	Type	Value
Butane (CAS 106-97-8)	15 minute	1250 ppm
	8 hour	1000 ppm

#### US. ACGIH Threshold Limit Values

Components	Type	Value
Butane (CAS 106-97-8)	STEL	1000 ppm

#### US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Butane (CAS 106-97-8)	TWA	1900 mg/m <sup>3</sup> 800 ppm

### Biological limit values

No biological exposure limits noted for the ingredient(s).

### Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

**Individual protection measures, such as personal protective equipment**

<b>Eye/face protection</b>	Wear safety glasses with side shields (or goggles).
<b>Skin protection</b>	
<b>Hand protection</b>	Impervious gloves. Confirm with reputable supplier first.
<b>Other</b>	Wear suitable protective clothing. As required by employer code.
<b>Respiratory protection</b>	Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2).
<b>Thermal hazards</b>	Not applicable.
<b>General hygiene considerations</b>	When using do not smoke. When using do not eat or drink.

---

**9. Physical and chemical properties**

---

<b>Appearance</b>	Clear
<b>Physical state</b>	Gas.
<b>Form</b>	Liquefied gas
<b>Color</b>	Clear
<b>Odor</b>	sulfur
<b>Odor threshold</b>	Not available.
<b>pH</b>	Not available.
<b>Melting point/freezing point</b>	Not available.
<b>Initial boiling point and boiling range</b>	< 35.6 °F (< 2 °C)
<b>Pour point</b>	Not available.
<b>Specific gravity</b>	Not available.
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Flash point</b>	-76.0 °F (-60.0 °C)
<b>Evaporation rate</b>	Not available.
<b>Flammability (solid, gas)</b>	Flammable gas.
<b>Upper/lower flammability or explosive limits</b>	
<b>Explosive limit - lower (%)</b>	1.9
<b>Explosive limit - upper (%)</b>	8.5
<b>Vapor pressure</b>	Not available.
<b>Vapor density</b>	> 1 (heavier)
<b>Relative density</b>	Not available.
<b>Solubility(ies)</b>	Not miscible
<b>Auto-ignition temperature</b>	549 °F (287.22 °C)
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Other information</b>	
<b>Explosive properties</b>	Not explosive.
<b>Oxidizing properties</b>	Not oxidizing.

---

**10. Stability and reactivity**

---

<b>Reactivity</b>	This product may react with strong oxidizing agents.
<b>Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Conditions to avoid</b>	Avoid heat, sparks, open flames and other ignition sources. Do not mix with other chemicals.
<b>Incompatible materials</b>	Strong oxidizing agents. Nitrates. Fluorine. Chlorine.
<b>Hazardous decomposition products</b>	May include and are not limited to: Oxides of carbon.

---

## 11. Toxicological information

---

<b>Routes of exposure</b>	Eye, Skin contact, Inhalation, Ingestion.	
<b>Information on likely routes of exposure</b>		
<b>Ingestion</b>	May cause stomach distress, nausea or vomiting.	
<b>Inhalation</b>	No adverse effects due to inhalation are expected.	
<b>Skin contact</b>	Contact with liquid may cause frostbite.	
<b>Eye contact</b>	Direct contact with eyes may cause temporary irritation. Contact with liquid may cause frostbite.	
<b>Symptoms related to the physical, chemical and toxicological characteristics</b>	Contact with liquefied gas might cause frostbites, in some cases with tissue damage. Asphyxiation may bring about unconsciousness without warning and so rapidly that victim may be unable to protect themselves.	
<b>Information on toxicological effects</b>		
<b>Acute toxicity</b>	asphyxia	
<b>Components</b>	<b>Species</b>	<b>Test Results</b>
Butane (CAS 106-97-8)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Not available	
<i>Inhalation</i>		
LC50	Rat	1443 mg/L, 15 Minutes, ECHA
<i>Oral</i>		
LD50	Not available	
<b>Skin corrosion/irritation</b>	Prolonged skin contact may cause temporary irritation. Contact with liquid may cause frostbite.	
<b>Exposure minutes</b>	Not available.	
<b>Erythema value</b>	Not available.	
<b>Oedema value</b>	Not available.	
<b>Serious eye damage/eye irritation</b>	Contact with liquid may cause frostbite.	
<b>Corneal opacity value</b>	Not available.	
<b>Iris lesion value</b>	Not available.	
<b>Conjunctival reddening value</b>	Not available.	
<b>Conjunctival oedema value</b>	Not available.	
<b>Recover days</b>	Not available.	
<b>Respiratory or skin sensitization</b>		
<b>Respiratory sensitization</b>	Not a respiratory sensitizer.	
<b>Skin sensitization</b>	This product is not expected to cause skin sensitization.	
<b>Mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
<b>Carcinogenicity</b>		
<b>OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)</b>		
Not listed.		
<b>Reproductive toxicity</b>	This product is not expected to cause reproductive or developmental effects.	
<b>Teratogenicity</b>	Not available.	
<b>Specific target organ toxicity - single exposure</b>	Not classified.	
<b>Specific target organ toxicity - repeated exposure</b>	Not classified.	
<b>Aspiration hazard</b>	Not likely, due to the form of the product.	

---

## 12. Ecological information

---

<b>Ecotoxicity</b>	Not available.
<b>Persistence and degradability</b>	No data is available on the degradability of this product.
<b>Bioaccumulative potential</b>	
<b>Mobility in soil</b>	No data available.
<b>Mobility in general</b>	Not available.

**Other adverse effects**

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

### 13. Disposal considerations

<b>Disposal instructions</b>	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose in accordance with all applicable regulations.
<b>Local disposal regulations</b>	Dispose in accordance with all applicable regulations.
<b>Hazardous waste code</b>	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
<b>Waste from residues / unused products</b>	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
<b>Contaminated packaging</b>	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

### 14. Transport information

**Transport of Dangerous Goods (TDG) Proof of Classification** Classification Method: Classified as per Part 2, Sections 2.1 – 2.8 of the Transportation of Dangerous Goods Regulations. If applicable, the technical name and the classification of the product will appear below.

**U.S. Department of Transportation (DOT)**

**Basic shipping requirements:**

**UN number** UN1011  
**Proper shipping name** Butane see also Petroleum gases, liquefied  
**Hazard class** 2.1

**Transportation of Dangerous Goods (TDG - Canada)**

**Basic shipping requirements:**

**UN number** UN1075  
**Proper shipping name** PETROLEUM GASES, LIQUEFIED  
**Hazard class** 2.1

**DOT**



**TDG**



### 15. Regulatory information

**Canadian federal regulations** This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

**Canada DSL Challenge Substances: Listed substance**

Butane (CAS 106-97-8) Listed.

**Canada NPRI VOCs with Additional Reporting Requirements: Mass reporting threshold/Identification Number**

Butane (CAS 106-97-8) 1 TONNES

**Export Control List (CEPA 1999, Schedule 3)**

Not listed.

**Greenhouse Gases**

Not listed.

**Precursor Control Regulations**

Not regulated.

**WHMIS 2015 Exemptions**

Not applicable

**US federal regulations**

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)**

Butane (CAS 106-97-8)

Listed.

**SARA 304 Emergency release notification**

Not regulated.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)**

Not listed.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)****SARA 302 Extremely hazardous substance**

No

**Classified hazard categories**Flammable (gases, aerosols, liquids, or solids)  
Gas under pressure  
Simple asphyxiant**SARA 313 (TRI reporting)**

Not regulated.

**Other federal regulations****Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Butane (CAS 106-97-8)

**US state regulations**

See below

**US - California Hazardous Substances (Director's): Listed substance**

Butane (CAS 106-97-8)

Listed.

**US - Illinois Chemical Safety Act: Listed substance**

Butane (CAS 106-97-8)

**US - Minnesota Haz Subs: Listed substance**

Butane (CAS 106-97-8)

Listed.

**US - Texas Effects Screening Levels: Listed substance**

Butane (CAS 106-97-8)

Listed.

**US. Massachusetts RTK - Substance List**

Butane (CAS 106-97-8)

**US. New Jersey Worker and Community Right-to-Know Act**

Butane (CAS 106-97-8)

**US. Pennsylvania Worker and Community Right-to-Know Law**

Butane (CAS 106-97-8)

**US. Rhode Island RTK**

Butane (CAS 106-97-8)

**US. California Proposition 65**

This product is not subject to warning labeling under the California Proposition 65 regulation.

**Inventory status**


Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

## 16. Other information

LEGEND	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

HEALTH	/ 2
FLAMMABILITY	4
PHYSICAL HAZARD	1
PERSONAL PROTECTION	X



### Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

### Issue date

29-April-2022

### Version #

01

### Effective date

25-April-2022

### Prepared by

Dell Tech Laboratories Ltd. Phone: (519) 858-5021

### Further information

Not available.

### Other information

For an updated SDS, please contact the supplier/manufacturer listed on the first page of the document.