

SAFETY DATA SHEET

SECTION 1: IDENTIFICATION

Product identifier used on the label:

Dri-Clave VK-3 Plaster and Stone Remover Product Name:

50036206, 50036206CN Product Code:

SDS Manufacturer Number: D002

 $\underline{\hbox{Other means of identification:}}$

Synonyms: Not applicable

Recommended use of the chemical and restrictions on use:

Product Use/Restriction: Plaster and stone removing ultrasonic cleaner.

 $\underline{\hbox{Chemical manufacturer address and telephone number:}}\\$

Manufacturer Name: Kulzer, LLC (Mitsui Chemicals Group)

Address: 4315 South Lafayette Blvd South Bend, Indiana 46614-2517

USA

General Phone Number: 800-431-1785

Emergency phone number:

Emergency Phone Number: Chemtrec @ 1-800-424-9300

SECTION 2: HAZARD(S) IDENTIFICATION

 $\underline{\textit{Classification of the chemical in accordance with CFR 1910.1200(d)(f):}\\$

Signal Word: Not applicable.

GHS Class: Not classified as hazardous according to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Hazard Statements: None. Precautionary Statements: None.

 $\underline{\text{Hazards not otherwise classified that have been identified during the classification process:} \\$

Route of Exposure: Eyes. Skin. Inhalation. Ingestion.

Potential Health Effects:

May cause irritation. Skin: May cause irritation.

Inhalation: Prolonged or excessive inhalation may cause respiratory tract irritation.

Inaestion: Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Eyes. Skin. Respiratory system. Digestive system. Target Organs:

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures:

Chemical Name CAS# **Ingredient Percent** EC Num.

Tetrasodium Ethylenediamine tetra acetic acid (EDTA) 64-02-8 1 - 5 by weight

Notes: The remaining components of this product are non-hazardous or are in a small enough quantity as to

not meet regulatory thresholds for disclosure.

SECTION 4: FIRST AID MEASURES

Description of necessary measures:

If symptoms develop Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Eye Contact:

If symptoms develop Wash skin with soap and plenty of water.

Dri-Clave VK-3 Plaster and Stone Remover Product Code: D002

Revision:: 3/28/17

Get medical attention if irritation develops or persists.

Inhalation: If symptoms persist, call a physician.

If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give Ingestion:

anything by mouth to an unconscious person

SECTION 5: FIRE FIGHTING MEASURES

Suitable and unsuitable extinguishing media:

Suitable Extinguishing Media: Use dry chemical or foam when fighting fires involving this material. Water mist may be used to cool

closed containers.

Special protective equipment and precautions for fire-fighters:

Protective Equipment: As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent)

and full protective gear.

Evacuate area of unprotected personnel. Use cold water spray to cool fire exposed containers to minimize risk of rupture. Do not enter confined fire space without full protective gear. If possible, Fire Fighting Instructions:

contain fire run-off water.

NFPA Ratings:

NFPA Health: 1 NFPA Flammability: 1 NFPA Reactivity: n



SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:

Personal Precautions: For large spills Evacuate area and keep unnecessary and unprotected personnel from entering the spill

Environmental precautions:

Environmental Precautions: For large spills Avoid runoff into storm sewers, ditches, and waterways.

Methods and materials for containment and cleaning up:

For large spills Contain spills with an inert absorbent material such as soil, sand or oil dry. Methods for containment:

For large spills Place into a suitable container for disposal. Methods for cleanup:

SECTION 7: HANDLING and STORAGE

Precautions for safe handling:

Handling: Use with adequate ventilation. Avoid breathing vapor, aerosol or mist.

Hygiene Practices: Wash thoroughly after handling. Avoid contact with eyes.

Special Handling Procedures: Do not re-use empty containers.

Conditions for safe storage, including any incompatibilities:

Storage: Store in a cool, dry, well ventilated area away from sources of heat and incompatible materials. Keep

container tightly closed when not in use.

SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION

EXPOSURE GUIDELINES:

Appropriate engineering controls:

Engineering Controls: No special protective equipment required under normal conditions of use. Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control

airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective

equipment.

Individual protection measures:

Eye/Face Protection: No special protective equipment required under normal conditions of use. If splashes are likely to

occur, wear: Chemical splash goggles.

Skin Protection Description: No special protective equipment required under normal conditions of use.

No special protective equipment required under normal conditions of use. No personal respiratory protective equipment is normally required. The need for respiratory protection will vary according to the Respiratory Protection:

airborne concentrations and environmental conditions (such as in manufacturing).

Product Code: D002



SECTION 9: PHYSICAL and CHEMICAL PROPERTIES

PHYSICAL AND CHEMICAL PROPERTIES:

Physical State: Liauid.

Color: Transparent pink

Odorless. Odor:

Odor Threshold: Not determined. Boiling Point: 215°C (419) °F Melting Point: Not determined.

Specific Gravity: 1.09 (Ref: water = 1).

Solubility: Very soluble. Vapor Density: Not determined. Vapor Pressure: Not determined.

Percent Volatile: 88%

Evaporation Rate: Not determined. pH: 13.3 - 13.6 Viscosity: Not determined. Coefficient of Water/Oil Not determined.

Distribution:

Flammability: Not determined. Flash Point: 210 °F (99°C)

Tag Closed Cup (T.C.C). Flash Point Method:

 $Lower\ Flam mable/Explosive\ Limit:$ Not determined. Upper Flammable/Explosive Limit: Not determined. Auto Ignition Temperature: Not determined. Oxidizing Properties: Not determined. VOC Content: Not determined.

SECTION 10: STABILITY and REACTIVITY

Chemical Stability:

Chemical Stability: Stable under recommended handling and storage conditions.

Possibility of hazardous reactions:

Hazardous Polymerization: Will not occur.

Conditions To Avoid:

Conditions to Avoid: Avoid contact with incompatible materials.

Incompatible Materials:

Incompatible Materials: Strong acids.

SECTION 11: TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION:

<u>Tetrasodium Ethylenediamine tetra acetic acid (EDTA)</u>:

Eye:

Administration into the eye - Rabbit Standard Draize test: 1900 ug [Not reported.] Administration into the eye - Rabbit Standard Draize test: 100 mg/24H [Moderate] (RTECS)

Product Code: D002

Oral - Rat LD50 - Lethal dose, 50 percent kill: 10~gm/kg [Details of toxic effects not reported other than lethal dose value] (RTECS) Ingestion:

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity:

Ecotoxicity: No environmental information found for this product. Environmental Fate: No environmental information found for this product.

SECTION 13: DISPOSAL CONSIDERATIONS

Description of waste:

Waste Disposal: Dispose of in accordance with Local, State, Federal and Provincial regulations.

SECTION 14: TRANSPORT INFORMATION

DOT Shipping Name: Not regulated DOT UN Number: Not Applicable DOT Hazard Class: Not Applicable

Notes: The data provided in this section is for information only. Please apply the appropriate regulations to

properly classify your shipment.

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations specific for the product:

TSCA Inventory Status: All the constituents of this product are TSCA listed or exempt from listing.

SARA: This product does not contain any chemicals which are subject to the reporting requirements of the

Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III (40CFR, Part 372)

California PROP 65: The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

This product does not contain any Proposition 65 chemicals.

Tetrasodium Ethylenediamine tetra acetic acid (EDTA):

TSCA Inventory Status: Listed Canada DSL: Listed

SECTION 16: ADDITIONAL INFORMATION

HMIS Ratings:

HMIS Health Hazard: 1 HMIS Fire Hazard: 1 HMIS Reactivity: n HMIS Personal Protection:

Health Hazard	1
Fire Hazard	1
Reactivity	0
Personal Protection	х

Other Information:

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the Autional Paint & Coatings Association (NPCA). The customer is responsible for determining the appropriate PPE to be used for the

task.

The National Fire Protection Association (NFPA) rating system is based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. NFPA hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. NFPA hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. The NFPA system is intended to be interpreted and applied only by properly trained individuals to identify fire, health, and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

SDS Revision Date: March 28, 2017

SDS Revision Notes: Supercedes MSDS 5/1/2015 SDS Author: Regulatory department

Copyright© 1996-2015 Actio Corporation. All Rights Reserved.

Product Code: D002

Dri-Clave VK-3 Plaster and Stone Remover

Revision:: 3/28/17