

Safety Data Sheet

Copyright, 2022, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 05-6730-5
 Version Number:
 26.03

 Issue Date:
 11/16/22
 Supercedes Date:
 03/02/20

SECTION 1: Identification

1.1. Product identifier

3MTM RelyXTM Luting Cement Liquid (3505L, 3515L)

Product Identification Numbers

70-2010-2502-3, 70-2010-2674-0, 70-2010-2698-9, 70-2010-3120-3, 70-2014-2056-2 7000054230, 7100111748, 7100111792, 7100111794

1.2. Recommended use and restrictions on use

Recommended use

Dental Product, Cement

Restrictions on use

For use only by dental professionals

1.3. Supplier's details

MANUFACTURER: 3M

DIVISION: Oral Care Solutions Division

ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA

Telephone: 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

2.1. Hazard classification

Serious Eye Damage/Irritation: Category 2B. Skin Sensitizer: Category 1.

2.2. Label elements

Signal word

Warning

Symbols

Exclamation mark |

Pictograms



Hazard Statements

Causes eye irritation.

May cause an allergic skin reaction.

Precautionary Statements

Prevention:

Avoid breathing vapors.

Wear protective gloves.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

SECTION 3: Composition/information on ingredients

| Ingredient | C.A.S. No. | % by Wt |
|---|------------|------------------------|
| Copolymer of Acrylic and Itaconic Acids | 25948-33-8 | 30 - 40 Trade Secret * |
| Water | 7732-18-5 | 30 - 40 Trade Secret * |
| 2-Hydroxyethyl Methacrylate (HEMA) | 868-77-9 | 25 - 35 Trade Secret * |
| Ethyl Acetate | 141-78-6 | < 2 Trade Secret * |

^{*}The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

SubstanceConditionCarbon monoxideDuring CombustionCarbon dioxideDuring Combustion

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with water. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

A no-touch technique is recommended. If skin contact occurs, wash skin with soap and water. Acrylates may penetrate commonly-used gloves. If product contacts glove, remove and discard glove, wash hands immediately with soap and water and then re-glove. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Do not get in eyes.

7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|---------------|------------|--------|-------------------------|---------------------|
| Ethyl Acetate | 141-78-6 | ACGIH | TWA:400 ppm | |
| Ethyl Acetate | 141-78-6 | OSHA | TWA:1400 mg/m3(400 ppm) | |

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use in a well-ventilated area.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Skin/hand protection

See Section 7.1 for additional information on skin protection.

Respiratory protection

None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state Liquid

Color Transparent Yellow

Specific Physical Form: Liquid

Odor Slight Odor, Sweet Odor Odor threshold No Data Available

pH2.2 - 3.2Melting pointNot ApplicableBoiling PointNo Data Available

Flash Point 104 °C [Test Method: Tagliabue Closed Cup]

Evaporation rateNo Data AvailableFlammability (solid, gas)Not ApplicableFlammable Limits(LEL)Not Applicable

3MTM RelyXTM Luting Cement Liquid (3505L, 3515L)

11/16/22

Flammable Limits(UEL)

Not Applicable

Vapor Pressure<=16 psia [@ 131.0 °F] **Vapor Density**No Data Available

Density 1.2 g/ml

Specific Gravity 1.2 [Ref Std:WATER=1]

Solubility in Water Complete

Solubility- non-water No Data Available Partition coefficient: n-octanol/ water Not Applicable No Data Available **Autoignition temperature Decomposition temperature** No Data Available Viscosity 175 - 225 centistoke Molecular weight No Data Available **Volatile Organic Compounds** No Data Available Percent volatile No Data Available **VOC Less H2O & Exempt Solvents** No Data Available

SECTION 10: Stability and reactivity

10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

Substance Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

The information below represents toxicological information associated with the individual components of the uncured product. Once properly mixed and/or cured, the product is safe for its intended use.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|---|-------------|-------------------|--|
| Overall product | Ingestion | | No data available; calculated ATE >5,000 mg/kg |
| Copolymer of Acrylic and Itaconic Acids | Ingestion | Rat | LD50 > 5,000 mg/kg |
| Copolymer of Acrylic and Itaconic Acids | Dermal | similar | LD50 estimated to be > 5,000 mg/kg |
| | | health hazards | |
| 2-Hydroxyethyl Methacrylate (HEMA) | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| 2-Hydroxyethyl Methacrylate (HEMA) | Ingestion | Rat | LD50 5,564 mg/kg |
| Ethyl Acetate | Dermal | Rabbit | LD50 > 18,000 mg/kg |
| Ethyl Acetate | Inhalation- | Rat | LC50 70.5 mg/l |
| | Vapor (4 | | |
| | hours) | | |
| Ethyl Acetate | Ingestion | Rat | LD50 5,620 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|------------------------------------|---------|--------------------|
| 2-Hydroxyethyl Methacrylate (HEMA) | Rabbit | Minimal irritation |
| Ethyl Acetate | Rabbit | Minimal irritation |

Serious Eye Damage/Irritation

| 20110 00 | | |
|------------------------------------|---------|-------------------|
| Name | Species | Value |
| 2-Hydroxyethyl Methacrylate (HEMA) | Rabbit | Moderate irritant |
| Ethyl Acetate | Rabbit | Mild irritant |

Skin Sensitization

| Name | Species | Value |
|------------------------------------|---------|----------------|
| 2-Hydroxyethyl Methacrylate (HEMA) | Human | Sensitizing |
| | and | |
| | animal | |
| Ethyl Acetate | Guinea | Not classified |
| | pig | |

Respiratory Sensitization

Page 6 of 9

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

| Name | Route | Value |
|------------------------------------|----------|--|
| 2-Hydroxyethyl Methacrylate (HEMA) | In vivo | Not mutagenic |
| 2-Hydroxyethyl Methacrylate (HEMA) | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Ethyl Acetate | In Vitro | Not mutagenic |
| Ethyl Acetate | In vivo | Not mutagenic |

Carcinogenicity

For the component/components, either no data are currently available or the data are not sufficient for classification.

Reproductive Toxicity

Reproductive and/or Developmental Effects

| Name | Route | Value | Species | Test Result | Exposure Duration |
|------------------------------------|-----------|--|---------|--------------------------|------------------------------|
| 2-Hydroxyethyl Methacrylate (HEMA) | Ingestion | Not classified for female reproduction | Rat | NOAEL 1,000 mg/kg/day | premating & during gestation |
| 2-Hydroxyethyl Methacrylate (HEMA) | Ingestion | Not classified for male reproduction | Rat | NOAEL 1,000 mg/kg/day | 49 days |
| 2-Hydroxyethyl Methacrylate (HEMA) | Ingestion | Not classified for development | Rat | NOAEL 1,000 mg/kg/day | premating & during gestation |

Target Organ(s)

Specific Target Organ Toxicity - single exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|--|------------|--------------------------------------|--|---------|------------------------|----------------------|
| Copolymer of Acrylic and Itaconic Acids | Ingestion | nervous system | Not classified | Rat | NOAEL 5,000 mg/kg | |
| Ethyl Acetate | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human | NOAEL Not available | |
| Ethyl Acetate | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | Human | NOAEL Not available | |
| Ethyl Acetate | Ingestion | central nervous system depression | May cause drowsiness or dizziness | Human | NOAEL Not available | |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|--|------------|--|----------------|---------|-----------------------------|-------------------|
| Copolymer of Acrylic and Itaconic Acids | Ingestion | endocrine system hematopoietic system liver | Not classified | Rat | NOAEL 200 mg/kg/day | 28 days |
| Copolymer of Acrylic and Itaconic Acids | Ingestion | heart bone, teeth, nails, and/or hair immune system muscles nervous system eyes kidney and/or bladder respiratory system vascular system | Not classified | Rat | NOAEL 2,000 mg/kg/day | 28 days |
| Ethyl Acetate | Inhalation | endocrine system liver nervous system | Not classified | Rat | NOAEL 0.043 mg/l | 90 days |
| Ethyl Acetate | Inhalation | hematopoietic system | Not classified | Rabbit | LOAEL 16 mg/l | 40 days |

| Ethyl Acetate | Ingestion | hematopoietic | Not classified | Rat | NOAEL | 90 days |
|---------------|-----------|----------------|----------------|-----|-----------|---------|
| - | | system liver | | | 3,600 | |
| | | kidney and/or | | | mg/kg/day | |
| | | bladder | | | | |

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

| Physical Hazards | |
|------------------|--|
| Not applicable | |

Health Hazards

Respiratory or Skin Sensitization

Serious eye damage or eye irritation

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

 Document Group:
 05-6730-5
 Version Number:
 26.03

 Issue Date:
 11/16/22
 Supercedes Date:
 03/02/20

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com