

SAFETY DATA SHEET

TARTAR, LIGHT STAIN & PERMANENT CEMENT REMOVER PCN 232,231

Use: Ultrasonic Cleaning Solution. Use as is.

Manufacturer: L&R Manufacturing Company, 577 Elm Street, P.O. Box 607 Kearny, NJ 07032-0607 USA. Publication

Date: 05/04/2018 REV: P

Product information call 201-991-5330 www.lrultrasonics.com

For emergencies involving a spill, leak fire or accident contact CHEMTEL 800-255-3924 within the United States. Or 1-813-248-0585 for International calls.

1. HAZARDS IDENTIFICATION



WARNING! CORROSIVES, IRRITANT. HARMFUL IF SWALLOWED.

Good industrial hygiene practices should be used when handling this material.

Acute Eyes: Direct contact causes irritation, redness and possible tearing.

Acute Skin: Prolonged or repeated contact causes redness, and drying of the skin.

Acute Inhalation: Breathing high concentrations of vapors or mists may cause irritation to the nose and throat.

Acute Ingestion: Product is acidic and will cause irritation to the stomach and mucous membranes.

B: POTENTIAL HEALTH EFFECTS:

Chronic Effects: This product does not contain any ingredient designated by IARC, NTP, ACGIH or OSHA as probable or suspected human carcinogen.

Do not use directly in the tank.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS Number	Percentage
Water	7732-18-5	80 - 88
Amidosulfamic Acid	5329-14-6	10 -15
Sodium 2-Ethylhexyl Sulfate	126-92-1	1 - 5
The exact concentration of composition has been withheld as a trade secret.		

4. FIRST AID MEASURES

Eye Exposure: Hold eyelids open and flush with a steady, gentle stream of water for at least 15 minutes. Seek medical attention.

Skin Exposure: Wash thoroughly with water. If irritation or redness develops, seek medical attention.

Inhalation: If respiratory irritation or distress occurs, move victim to fresh air. Seek medical attention if respiratory irritation or distress continues.

Ingestion: Seek immediate medical attention. DO NOT INDUCE VOMITING, Give large quantities of water if conscious. MEDICAL CONDITIONS POSSIBLY AGGRAVATED BY EXPOSURE: Skin contact may aggravate existing skin disease.

5. FIRE FIGHTING MEASURES

FIRE HAZARD DATA: NOT COMBUSTIBLE

Suitable Extinguishing Media: Extinguish surrounding fire with dry chemical, CO2 or a BC/ABC extinguisher.

Special Fire Fighting Procedures: None known

Unusual Fire and Explosion Hazards: Closed containers may burst due to build up of pressure when exposed to extreme heat.

Hazardous Decomposition Materials: (under fire conditions) None known.

6. ACCIDENTAL RELEASE MEASURES

Cleanup and Disposal of Spill: May be neutralized with baking soda/baking powder. Mop up spill and dispose of by dilution to a sanitary sewer system as permitted by local, state and federal regulations.

Regulatory Reporting: Not required

7. HANDLING AND STORAGE

Minimum/Maximum Storage Temperatures: 40°F to 100o F, 4°C to 88°C. Protect from freezing. Freezing will cause crystallization of this product. Product may be thawed in hot water and then mixed vigorous

8. EXPOSURE CONTROL/PERSONAL PROTECTION

General: These recommendations provide general guidance for handling of this product. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. When developing safe handling procedures, do not overlook the need to clean and dispose of the material. Waste resulting from the use of this product should be handled in accordance with Section 13: Disposal Considerations.

Exposure Guidelines: Exposure limits are recommended worker breathing limits. The following limits apply to this material:

INGREDIENTS LIMITS INGREDIENTS LIMITS
Amidosulfamic Acid None established Sodium 2-Ethylhexyl Sulfate none established

Engineering Controls: Normal room ventilation.

Respiratory Controls: For reasonable uses of this material, respiratory protection should not be necessary.

Eye/Face Protection: Safety glasses to protect from splashing.

Skin Protection: Rubber or plastic gloves to avoid drying and irritation to the skin.

Work Practice Control: Normal hygiene in the work area should be taken when working with or handling this product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Clear liquid Color: Colorless pH: 1.2 as supplied

Water Solubility: Soluble Freezing Point Range: $< 32^{\circ}F, 0^{\circ}C$ Vapor Pressure: Not established

Specific Gravity: 1.07

Melting Point Range: Not available Boiling Point: Approx. 212 °F, 100 °C

Vapor Density: Not established

Flash Point: None to boiling Method: Tag Closed Cup A

Flammability limits (vol/vol %): Lower: No Data Upper: No Data Viscosity: Similar to water

Odor: Mild Sweet odor Odor Threshold: Not available Evaporation Rate: Not Applicable

Partition Coefficient; n-octanol / water: Not available

Decomposition Temperature: Not available uto Ignition Temperature: Not available

V.O.C. (calculated): < 0.05 lbs. / gal or < 5 grams / 1.

Percent volatile by volume: Approx. 85% as water 10. STABILITY AND REACTIVITY

Chemical Stability: Stable

Conditions to be avoided: Excessive heat.

Materials/Chemicals to be avoided: Strong bases, nitrates, nitrites, chlorates, chlorine, hypochlorite, cyanides or sulfides.

Decomposition Type: Thermal: May release oxides of sulfur or ammonia gases.

Possibility of Hazardous Reactions: WILL NOT OCCUR r

11. TOXICOLOGICAL INFORMATION

Acute Eye Irritation: Irritating to eyes.

Acute Skin Irritation: No test data found for product. Acute Dermal Toxicity: No test data found for product. Acute Respiratory Irritation: No test data found for product. Acute Inhalation Toxicity: May cause nose and throat irritation. Acute Oral Toxicity: Sulfamic Acid, LD50 rat = 3160 mg/kg

Sodium 2-Ethylhexyl Sulfate, LD50 rat = 4 grams/kg

Chronic Toxicity: This product does not contain any substances that are considered by OSHA, NTP, IARC OR ACGIH to be a probable or suspected human carcinogen. No additional test data was found for this product.

12. ECOLOGICAL INFORMATION

Ecotoxicological Information: No data found.

13. DISPOSAL CONSIDERATIONS

This product can be disposed in sanitary sewer system, with dilution, where permitted by local, federal and state regulations. Product can be neutralized with baking soda (sodium bicarbonate) to a neutral pH.

14. TRANSPORTATION INFORMATION

For domestic ground shippers, product is classified as Limited Quantity of one (1) gallon or less shipped by domestic ground transportation. For all other shippers, containers: Corrosive liquid, n.o.s. FOR EXPORT: Corrosive liquid, Acidic, inorganic n.o.s. (contains Sulfamic Acid), UN3264, 8, Packing Group III, EMS 8-15 Do not stack cartons more than five high.

15. REGULATORY INFORMATION

Inventory Issues: All components of this product are listed on the U.S. TSCA, Canadian DSL, European EINECS/ELINS chemical listings.

16. OTHER INFORMATION

National Fire Protection Association

Hazard Rating, NFPA

Health

Flammability

Reactivity

Special

SDS CHANGES

DATE 05/04/2018 DESCRIPTION OF CHANGE

Emergency Contact Change

Disclaimer: The information herein is given in good faith but no warranty expressed or implied is made. This SDS has been prepared by L&R Manufacturing Company.